

RENOLIT ALKORPLAN

INFORMATION SHEET

SELF ADHESIVE VCLS AND INSULATION BOARDS FOR BONDED SYSTEMS

SELF ADHESIVE VAPOUR CONTROL LAYERS FOR USE WITH STEEL, CONCRETE AND TIMBER DECKS.

RENOLIT ALKORPLUS₈₁₀₀₂ Vapour Barrier SK

Based on an aluminium foil-polyester material, employing a cold self adhesive glue, based on bitumen and rubber.

It has a peelable release paper. It can be used with insulation board which is bonded to it with PU glue. RENOLIT

ALKORPLUS₈₁₀₀₂ vapour barrier SK can be used on steel decks, concrete (cast in situ and pre-cast) aerated concrete and timber.

The roll sizes are: 1.2 mm thick, 1 mtr wide and 25 mtrs long, weight per square metre: 1.1 kg
The edges can be overlapped and stuck together.

INSULATION BOARDS TO BE USED WITH RENOLIT ALKORPLUS₈₁₀₀₂ VAPOUR BARRIER SK

PU or PIR foam boards with plain glass tissue, foil or unsanded bitumen facings. Board types are available from Kingspan, Ecotherm, Celotex, Rockwool SPA and Recticel.

Boards may be bonded to RENOLIT ALKORPLUS₈₁₀₀₂ with our RENOLIT ALKORPLUS adhesive, bitumen or Instastik. RENOLIT ALKORPLUS₈₁₀₆₈ is not suitable for bonding insulation boards to RENOLIT ALKORPLUS₈₁₀₀₂.

The use of adhesives with other insulation systems must be referred to RENOLIT Technical Dept.

WWW.ALKORPROOF.COM



RENOLIT (UK) Cramlington Ltd - Station Road, Cramlington, Northumberland NE23 8AQ - United Kingdom
T +44 1670 718283 - F +44 1670 590096 - renolit.cramlington@renolit.com

Rely on it.



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbphenin.com
www.hbphenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Militaire à côté de Toxi Lobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61