

paints Galvais decorative effects paints

Description:

GALVAIS consists of a special paint used to imitate old galvanised zinc. It is used both in interiors and exteriors. However, in exteriors, it is recommended to previously treat the support with an antioxidant primer.

Uses:

Features & benefits:

It is used to protect and decorate metallic supports.

Surface preparation:

The support of application must be clean, dry and free of grease.

Application:

- -Remover bien el contenido de los envases antes de usar.
- Apply with a paint brush, gun or airless equipment.
- Apply directly when using a paint brush or dilute 5 to 10% in DISOLUAIS-N.
- Apply with a gun by diluting 30% in DISOLUAIS-N.
- It is recommended to apply at least two coatings.

TechnicalFeatures:

Density: 1.6 ± 0.05 Kg/Litre at 20°C

Dry upon touching: Solid content in volume: 45 ± 1 %

Colour/s: old galvanised colour.

Coverage:

4 m2 per I.

Clean up:

Tools are cleaned using our greasy solvent DISOLUAIS N.

Storage:

It is recommended to store this product for 1 year in tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.





paints GalValS decorative effects paints

Packaging:

Available in packs of:

.: 0.25 L

0.75 L

4 L

Health and safety advice:

R20/21 -- Harmful by inhalation and in contact with skin

R38 -- Irritating to skin

R40 -- Limited evidence of a carcinogenic effect

R51/53 -- Toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment :

S15 -- Keep away from heat







The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.

