

Description:

PINTIS LISA consists of a plastic paint based on acrylic resins and selected inorganic pigments. It shows a great stability to light and is used for decorating and protecting interior supports.

Uses:

It is used on ceilings and walls, on mortar and cement based renders, plaster, gypsum, perli- plaster, etc.

Features & benefits:

GREAT COVERING POWER. EASY APPLICATION. GREAT STABILITY.

Surface preparation:

The support of application must be clean and dry, free of grease, dust, lime based, temper or oil based paints, by being compact.

Application:

- Apply using a paint brush, roller or gun.
- The first coating is applied by diluting 10 to 20% in water.
- The second coating is applied without diluting.
- A satin finish is achieved using ACRILAIS TRASLUCIDO diluted to 30%.
- IMPRIMAIS SUPER, IMPRIMAIS M.U. or IMPRIMAIS NORMAL primer is used (depending on the type of support).

Technical Features:

Density: 1.6 Kg/Litre \pm 0,05
Viscosity: 42.500 \pm 7.500 mPa.s
Dry for repainting: 8 Hours/50 micron/20°C/65% of R.H.
-: Easy application and washing.
-: Good paint brush application and great covering power.
-: Resistant to alkalis and attrition caused upon abrasion.
-: Totally soluble in water and dyeable with TINTAIS.
Aspect: smooth and matt.
Colour/s: blanco nieve.

Coverage:

3 m² per kg.

Clean up:

Clean using large amounts of water.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hpbbenin.com
www.hpbbenin.com

DIRECTION COMMERCIALE
HBP New City
Moro Militaire à côté de Tosi Ibo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

Rojo, marron, musgo, verde and azul: 5 Kg
25 Kg

Marfil, ocre, salmon, coral and gris: 5 Kg
25 Kg

Blanco: 5 Kg
25 Kg

Health and safety advice :



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbphenin.com
www.hbphenin.com

DIRECTION COMMERCIALE
HBP New City
Mare Militaire à côté de Taxi Lobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61