

Description:

ESMAIS consists of a paint composed of oil based resins having a great covering power and light stable pigments. For interior and exterior use.

Uses:

Used to protect and decorate walls and different types of supports in interiors as well as exteriors.

Features & benefits:

EXCELLENT RESISTANCE.COLOUR STABLE.EASY APPLICATION.GREAT DURABILITY.

Surface preparation:

The background of application must be clean, free of grease and dry.

Application:

- Priming is applied onto the support as follows:
Antioxidant primer: IMPRIMACION XC, MINOAIS SUPER, etc. On metallic supports made of iron and steel.
IMPRIMAIS M.U.: on supports made of plaster, brick and mortar.
IMES: on supports made of wood.
IMPRIGAIS: on aluminium and galvanised supports.
- Mix the content of each package before using.
- Apply with a paint brush, roller or gun.
- When using a paint brush, apply directly or by slightly diluting in 5 to 10% in DISOLUAIS-B.
- Apply with a roller or gun by diluting 10 to 25% in DISOLUAIS.
- Inmersi?n, diluido de 25 al 40% con DISOLUAIS B.
- It is recommended to apply at least two coatings.

TechnicalFeatures:

Density: It varies depending on colour.
Solid content in volume: 50 ± 1 %
Dry for repainting: 8 to 10 Hours/20°C/65%
Vehicle: Oil based resins.
Pigments: Rutile titanium dioxide and other colours (depending on colour chart).
-: Stable to light and great resistance to bleakness.
-: Washable with water, detergents, turpentine, aliphatic solvents.
Aspect: brilliant or matt, smooth and continuous.
Colour/s: according to colour chart.

Coverage:

8 m2 per l and coating according to support.

Clean up:

Tools are cleaned using our greasy solvent DISOLUAIS.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hpbbenin.com
www.hpbbenin.com

DIRECTION COMMERCIALE
HBP New City
Moro Militaire à côté de Tosi Ijobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

Packaging:

Available in packs of:

Rojos: 0.25 L

0.75 L

4 L

20 L

Amarillos, verdes, malvas and azules: 0.25 L

0.75 L

4 L

20 L

Blancos, cremas, grises, ocre and negro: 0.25 L

0.75 L

4 L

20 L

Health and safety advice :

R33 -- Danger of cumulative effects

R40 -- Limited evidence of a carcinogenic effect

R61 -- May cause harm to the unborn child

R62 -- Possible risk of impaired fertility

S16 -- Keep away from sources of ignition - No smoking

S45 -- In case of accident or if you feel unwell seek medical advice immediately (show the label where possible)



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.