

## duroais capa continua

pavements restoration

## **Description:**

DUROAIS CAPA CONTINUA consists of a powder product to be mixed with AGLUTAIS and water or AGLUTAIS 30-50. It forms a quick setting levelling paste. It is ideal for continuous pavement with strong resistance to abrasion and bleakness.

#### Uses:

It is used for levelling surfaces(as long as irregularities do not exceed 2 to 3 mm thickness) in pavements in garages, parking areas, car repair garages, filling stations, etc.

#### Features & benefits:

EASY APPLICATION.SELF LEVELLING.EXCELLENT MECHANICAL RESISTANCE.ENHANCED RESISTANCE TO BLEAKNESS.

## Surface preparation:

The background of application must be clean, free of dust, grease, oil, salts or any substances that may hinder proper adherence. The support must be slightly damp during hot weather.

### **Application:**

- Preparation of the product:

DUROAIS CAPA CONTINUA is prepared using AGLUTAIS 30-50 in a proportion of 24 litres of AGLUTAIS 30-50 for every 100 kg of DUROAIS CAPA CONTINUA.

- Mix manually or by using a low speed mix(300-500 rpm).
- Pour the product by spreading with a serrated trowel in 3 to 10 mm thick layer. Irregularities must not exceed 2 to 3 mm thick coating.
- After setting, spray a thin layer of LACURIS so as to improve curing.

#### **TechnicalFeatures:**

Water absorption: 20 to 24%

Capillarity: Curing density: 1.750 to 1.800 kg/m3 Compressive resistance: > 180 kg/cm2 Flexural strength resistance: > 40 kg/cm2

Water retention: > 97%

## Coverage:

4.5 kg per m2 in 3mm thick coating.

#### Clean up:

Clean using large amounts of water.

#### Storage:

It is recommended to store this product for 2 years in tightly closed original packages protected against bleakness.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.





# duroais capa continua

pavements restoration

Packaging:

Available in packs of: .: 25 Kg

Health and safety advice:









The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.

