

### Description:

It consists of a mortar having no thixotropic retraction, based on cement with selected aggregates and additives to be mixed with water to form a mortar that is ideal for restoration in many applications.

### Uses:

It is used for repairing chippings, cavities, fissures and gravel lumps on concrete. It enables anchoring of cables, wood, metallic profiles, etc. Also for protecting metallic frameworks, ashlar-like structure for concrete slips, for sealing big passive cracks.

### Surface preparation:

The background of application must be clean, free of grease, dust or loose parts, by being compact and suitably dampened.

### Application:

- Mix directly with 20 % of water until obtaining a workable paste that can be easily applied.
- Apply using a normal trowel, spatula or manually (by wearing gloves).

### Technical Features:

Powder density: 1.350 ± 0.050 g/cc.  
Mass of density: 1.950 ± 0.050 g/cc.  
Curing density: 1.950 ± 0.050 g/cc.  
Water absorption: 20 ± 2%  
Capillarity: Water retention: > 97%  
Colour/s: gris cemento.  
Compressive resistance: 200 to 300 kg/cm<sup>2</sup>  
Flexural strength resistance: 70 kg/cm<sup>2</sup>

### Clean up:

Clean with large amounts of water.

### Features & benefits:

EXCELLENT ADHERENCE. IMPROVED MECHANICAL RESISTANCE. NO RETRACTION. THIXOTROPIC.

### Coverage:

2 kg per m<sup>2</sup> in 1 mm thick coating.

### Storage:

It is recommended to store this product for 2 years in its tightly closed original packages protected against bleakness and extreme temperatures in a cool dry place.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña  
Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE  
Jonquet Face MTN Internet  
Tél.: (+229) 21 33 33 48  
95 96 00 08

04 B P : 0526 Cotonou  
contact@hbpenin.com  
www.hbpenin.com

DIRECTION COMMERCIALE  
HBP New City  
Maro Militaire à côté de Taxi Lobo  
Tél.: (+229) 21 32 48 48  
95 02 72 72 - 94 00 61 61

**Packaging:**

Available in packs of:

**NORMAL:** 1 Kg

5 Kg

25 Kg

**Health and safety advice :**



The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



**PROFESSIONAL CONSTRUCTIVE SOLUTIONS**

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña

Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



DIRECTION GÉNÉRALE  
 Jonquet Face MTN Internet  
 Tél.: (+229) 21 33 33 48  
 95 96 00 08

04 B P : 0526 Cotonou  
 contact@hbpbenin.com  
 www.hbpbenin.com

DIRECTION COMMERCIALE  
 HBP New City  
 Maro Militaire à côté de Teij Tabo  
 Tél.: (+229) 21 32 48 48  
 95 02 72 72 - 94 00 61 61