

releasing agents deais standard

multipurpose desmouldants

Description:

DEAIS STANDARD is a releasing agent for wood and metallic moulds.

Uses:

It is used in all types of moulds(metallic, wooden, etc) by avoiding breaking risks when complex designed pieces are turned out.

Features & benefits:

SPECIALLY DESIGNED FOR WOOD AND METALLIC MOULDS.

Surface preparation:

The background of application must be clean, free of rust, concrete wastes as well as cement dust so as to prevent the formation of stains on concrete.

Application:

- Shake the content of each package thoroughly before using.

- It is hard applied(without diluting). In case of economizing, when using absorbent moulds(wood, etc), it is recommended to dilute in water or diesel oil in a proportion of 1:4 or 1:5.

- Apply using a paint brush, roller or spray before placing the metallic framework.
- Apply the product thoroughly onto the surfaces of the moulds.

TechnicalFeatures:

- -: It prevents adherence to concrete, mortars and renders, etc.
- -: It enables to save on labour used in cleaning and maintenance of mouldings
- (it reduces attrition).

-: Soluble en agua and diesel.

Density: 0.86 Kg/L ± 0.03 Colour/s: Marrón verdoso.

Clean up:

Clean using large amounts of water.

T E A I S

Packaging:

Available in packs of: .: 200 L 51 25 L 60 L



Storage:

Coverage:

50 m2 per I, diluted.

It is recommended to store the product for 1 year in its tightly closed original packages.

Health and safety advice :

R65 -- Harmful : may cause lung damage if swallowed

S60 -- This material and its container must be disposed of as hazardous waste S62 -- If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of it's useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS ©TEAIS S.A. - All rigths reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña Telf.: 981 600 966 - Fax: 981 601 508 - Email: info@teais.es



