

Description:

EMPLAIS M is a solvent based plaster used for wood. Its quality remains unaltered after its application.

Uses:

It is used for smoothing irregularities on wooden surfaces. For eliminating cracks, holes, fissures and imperfections in general.

Features & benefits:

Surface preparation:

The background of application must be clean, dry, free of dust, grease, oil and contaminating agents that may hinder the proper adherence of the product onto the support.

Application:

- It is hard applied on the surface to be treated until slightly going beyond the edges. Once dry, the support can then be sanded so as to achieve a perfect finish on the plastered piece.
- It dries quickly and can be sanded after 30 minutes since application under normal conditions.
- After using, close the package immediately so as to prevent the product from drying.

TechnicalFeatures:

Density: 1.1 g/cc ± 0.05
Colour/s: pino, nogal, roble, sapeli.

Coverage:

According to the application.

Clean up:

Clean using our solvent DINITRAIS.

Storage:

It is recommended to store this product for 2 years in tightly closed original packages, protected against bleakness.

Packaging:

Available in packs of:
.: 0.135 cc



Health and safety advice :

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.