



XTREM FORGED

1. DESCRIPTION

Product Type

Water-based antirust varnish with forged finish, for direct application on metals, without need for primer. It contains special ingredients such as a high-solid styrene-acrylic resin (20%) which provides the varnish with high resistance to rust, humidity and water, as well as excellent adherence on different surfaces. Its formula has preferred highly effective, non-dangerous pigments free of heavy metals, which act through ion exchange. While preventing the appearance of rust, they favour the creation of a protective coating on the metal, which neutralises the formation of iron oxide and avoids contact with aggressive agents on the surface.

Fields of Application

All types of metal surfaces

Advantages

- Anti-corrosive and antirust
- Oxide neutraliser
- Extraordinary adherence
- Direct application on rust
- May be applied directly on rusty surfaces after removing loose particles
- Forged finish
- Very fast drying. Second coat in 2 hours approx.
- Easy application. Excellent brushability
- Slight smell which disappears when dry
- Water-based
- Meets COV 2010 standard
- Contains laminated micaceous hematite which forms a waterproof barrier

Colours

Forged: Grey, Green and Black.

Packaging

750 ml and 4 litres.

2. USAGE GUIDE

Preparation

Apply on clean and dry surfaces. Remove any loose paint through stripping, scraping or sanding, as well as poorly adhered rust particles.

There is no need to apply an antirust or adherence primer.

May be applied on new or rusty surfaces, simply brushing to remove loose particles (ST-2 cleaning).

For greater rust removal, the application of a rust converter is recommended if ST-2 cleanliness cannot be achieved.

Application

Apply the product without diluting.

For high rust protection, apply at least two coats.

Apply with brush, spray gun and roller.

Cleaning Equipment

Water and soap.

3. TECHNICAL DATA

Density at 20° C: 1.30 ± 0.05 g/mL

Coverage: 5 m²/L, applying a minimum coat of 100 dry microns, equivalent to 2-3 thick coats

Drying in normal conditions: Less than 1 hour. Second coat: 2 hours.

Comparative tests with other solvent-based antirust varnishes have shown that OXIRITE XTREM provides greater protection against corrosion.

4. SPECIAL INDICATIONS

Do not store for long periods in temperatures under 5°C and over 30°C.

Do not apply in excessive heat or humidity conditions. Avoid spilling the product in watercourses. When using the product, take general protection and hygiene precautions.

For further information, see the label on the product and the Safety Data. This product is not dangerous according to the "Regulation on classification, packing and labelling of dangerous substances (R.D. 255/2003)". The safety data factsheet is available for all professional users on request.

5. QUALITY AND PERFORMANCE. QUALITY GUARANTEE

OXIRITE XTREM FORGED is a Xylazel product, developed with the highest degree of quality and reliability, which complies with the strictest manufacturing and control standards. It is a highly effective product, featuring innovative characteristics thanks to its production standards and exclusive ingredients, which ensure extraordinary performance. Xylazel S.A. guarantees the quality of the product, its efficiency and durability, providing that each and every specification contained in this technical factsheet is observed. Product of Spanish origin.

6. GENERAL CONDITIONS

The data provided are indicative and of a general nature. They provide a description of our products and inform the user on their application and instructions for use. Given that the working conditions and related materials are highly varied and different, it is understood that we cannot cover here all individual cases. If you should have any doubts, we recommend you test the product or consult our Technical Assistance Service.

We take responsibility for the invariably high quality of our products, in compliance with the provisions of our General Sales and Delivery Conditions.

CUSTOMER SERVICE

TEL.: +34 986 34 34 24
FAX: +34 986 34 64 24
a.villar@xylazel.com
t.giaz@xylazel.com



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Militaire à côté de Toxi Lobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24
FAX: +34 986 34 64 17
www.xylazel.com

