

xylazel®

RUST TRANSFORMER

1. DESCRIPTION

Product Type

Xylazel Rust Transformer is a water based primer that transforms rust in iron and steel surfaces.

No primer or undercoat required. It transforms surface into a sound black surface.

Xylazel Rust Transformer is for interior and exterior use.

It is suitable for any iron and steel surfaces such as doors, windows, handrails, railings etc.

Available in liquid and gel.

Liquid formulation is suitable for use on horizontal surfaces and gel formulation for vertical surfaces.

Advantages

- Xylazel Rust Remover transforms rust to a sound surface that can be overcoated.
- Apply direct onto rusty surfaces.
- Simply remove any loose rust or flakes and apply it.
- It can be recoated after 6 hours.
- Low odour formula. Once dried, it does not smell.

Colours

White. Once the product brings into contact with rust, it transform into a black finish.

Packaging

Liquid: 250 ml, 750 ml and 5 litres.
Gel: 125 ml and 750 ml.

2. TECHNICAL DATA

Viscosity

Low viscosity, liquid.

Reaction

Under normal conditions it reacts in 15 - 30 minutes.

Second coat: 6 hours.

Coverage: 20-25 m²/litre.

Cleaning Equipment:

Water.

Suitable Use Temperature:

From 8°C on up.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed.

Remove all loose rust or dirt with a wire brush or sand paper.

Rinse thoroughly with clean water and allow time to dry.

Application

Stir the product thoroughly.

Pour required amount into a plastic container.

Xylazel Rust Transformer is ready to use. Apply by brush direct to rusty area, working well into heavily pitted areas, corners and edges. Avoid coating onto painted areas. Xylazel Rust Transformer will turn black when reacting with rust. If it does not change colour in 1 hour re-apply.

Allow 6 hours approximately to dry. Apply topcoat.

Test a small area first for coating adhesion and/or compatibility.

4. OTHER INFORMATION

Do not store if the room temperature is below 5°C or over 30°C.

Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



DIRECTION GÉNÉRALE
longuet face MTN Internet
Tél.: (+229) 21 33 33 48
95 95 00 08

04 B.P. - 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Wilfride avenue de l'Est Lobo
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com

