

1. DESCRIPTION Product Type Xylazel Floor Paint is a water based protective paint for use on concrete floors. It is suitable for both interior and exterior use: garages, cellars, warehouses, gyms...

Advantages - Ideal for transforming dusty garage floors. - Ultra tough finish: resists scuffing and scraping.

Colour

Packaging

2. TECHNICAL DATA Drying Time: 15 minutes each coat. Density: 1,4 g/cm³. Thermoplastic resin. Inflammation point: 48°C. Cleaning equipment: Solvent.

3. USAGE GUIDE

Preparation The surface should be clean dry and free from dust and any loose material. Shake well, until ball rattles and

afterwards for 2 minutes.

Application

Hold can 20-25 cm away from stained area, commence spraying moving can in a motion from left to right or up and down until the area is covered with a thin and even coat. Do not apply a thick coat. One coat should be enough. Once the first coat is dried, after 15 minutes, if stain is still visible, a second coat can be applied. Test for compatibility. Do not apply if the room temperature is below 5°C. After use hold the spray-can in an upside down position and press the valve until the colourless propellant comes out.

This prevents blockage of the valve.

4. OTHER INFORMATION Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings. Do not store below 5°C or above 30°C. Not suitable for use in contact with drinking water or foodstuffs.

5. INFORMATION AND SERVICE Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control. Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



DIRECTION GÉNÉRALE Janquet Face MTN Internet Tél: (+229) 21 33 33 48 95 96 00 08



