



LONG LASTING TEAK OIL

1. DESCRIPTION

Product Type

Xylazel Long Lasting Teak Oil is a mixture of natural resins and oils to nourish and feed wood. It is suitable for teak and similar woods. Xylazel Long Lasting Teak Oil can help restore the appearance of old furniture and maintain the colour and appearance of new furniture.

Effectiveness

- Treated wood.
- Nourishes, feeds, seals and protects the natural beauty of exterior wood.
- It protects and enhances the wood by replacing the natural oils lost through weathering.
- It prevents greying.
- It protects the wood from stains and dust.
- Enhances the natural colour of the wood.

Advantages

- JUST ONE COAT EVERY 2 YEARS.
- The long-lasting formulation protects wood from the harmful effects of weathering.
- It enhances the wood by replacing the natural oils lost through weathering.
- Silky and natural finish.
- Quick Drying.
- Easy to apply. Excellent penetration into timber.
- Easy maintenance, there is no need to sand, simple clean surface dirt apply more Long Lasting Teak Oil.

- With Solar Filter.

Surfaces

Suitable for use on all hardwoods including teak, iroko and exotic woods. It protects hardwood garden furniture from the harmful effects of weathering for 2 years. Apply in bare wood.

Colours

Teak and Light Teak.

Packaging: 750 ml and 5 L.

2. TECHNICAL DATA

Drying times: 6 hours in normal weather conditions.
Second coat: 6 hours.
Density at 20°C: 0,86±0,01 g/ml.
Cleaning equipment
Xylazel Thinner.
Coverage: 12-18 m²/litre and coat. Coverage will vary dependent upon the porosity of the substrate.
Application: brush.

3. USAGE GUIDE

Preparation
Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed.
Ensure surface is free from varnish or other finishes.

Application

Shake the tin well before use.
Apply liberally using a brush.
Long Lasting Teak Oil is easy to apply, simply apply and allow

the oil to penetrate deep into wood for up to 30 minutes and wipe the surface dry with a clean, lint-free cloth. A second coat can be applied before the first coat is dry.

Allow to dry for 6 hours.

In case of doubt, try a test area first and allow to dry fully to ensure final appearance is acceptable.

4. OTHER INFORMATION

Do not store when room temperature is below 5°C or over 30°C.

Do not empty into drains or watercourses.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 00

04 B.P. - 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Moro Mikéle & route de l'Accès Libéré
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24
FAX: +34 986 34 64 17
www.xylazel.com

