

INDOOR VARNISH

1. DESCRIPTION

Product Type

A solvent-based interior varnish for use as a decoration and protection on smooth planed softwoods and hardwoods.

Effectiveness

Xylazel Indoor Varnish protects woods against scuffs and knocks. It is resistant to water and mild household detergents.

Xylazel Indoor Varnish brings out the inherent beauty of wood, enhancing the natural wood grain.

Advantages

- Excellent matt, satin and gloss finishes.
- It does not crack, peel or flake.
- Transparent finish.
- · Easy to apply.
- · Excellent levelling properties.
- Thixotropic.
- Touch drying: 2-4 hours.
- Excellent hardness and elasticity at the same time. It does not crack.
- Provides a non-yellowing finish for woodwork.
- Excellent coverage: 13-15 m²/litre per coat.
- Once dry, Xylazel Indoor Varnish does not increase the flammability of the wood.

Surfaces

Suitable for interior wood, cladding, beams, pillars, doors, frames, windows, fences, furniture, banisters, handrails, wood panelling, skirting and any piece of wood.

Colours

Matt: colourless. Satin: colourless.

Gloss: colourless, pine, pine oregon, cherry, oak, mahogany and walnut. Mixable colours.

125 ml, 375 ml, 750 ml, 4 litres (colourless only).

2. TECHNICAL DATA Density at 20°C:

Matt: 0,915-0,935 g/mL. Satin: 0,91-0,92 g/mL. Gloss: 0,897-0,919 g/mL. Coloured gloss: 0,895-0,920 g/mL.

Viscosity 20°C Brookfield:

Matt: 2-4 poises. Satin: 1,5-3,5 poises. Gloss: Thixotropic.

Inflammation point:

Matt: >39°C. Satin: >39°C Gloss: >45°C.

Average Gloss Matt: 60° 25 Satin: 60° 45

Gloss: 20° 80

Touch dry: 2/4 hours. Second coat: 6/12 hours aprox.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

It is deemed necessary to apply one or two coats of Xylazel Wood Preserver to provide protection against decay, damp and insects.

Bare wood

Ensure the wood is clean and dry. Apply 2 coats. Lightly sand and clean dust between coats.

For previously varnished wood Remove any coating in a loose or poor condition.

Apply 1 or 2 coats of Xylazel Indoor Varnish. Lightly sand and clean dust between coats.

Coverage

67-77 mL/m² aprox. per coat under normal conditions.

Application

Xylazel Indoor Varnish is ready to use, you should not dilute it with solvent or any other product.

Stir the product thoroughly. Apply by brush, roller, airless or spray gun. Xylazel Indoor Varnish should be flowed on with the minimum of brushing and finished in the direction of the grain. Recoat after 6-12 hours.

The can should be resealed after use and storage tightly closed to prevent evaporation of the product and entry of air.

Cleaning equipment Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Apply in well ventilated areas until the treated timber is dry.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Store in a cool, dry, well ventilated place away from heat and sources of ignition.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Packaging











36400 PORRIÑO (PONTEVEDRA)

CIALE
TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

WWW.xylazel.com

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n

