



OUTDOOR VARNISH

1. DESCRIPTION

Product Type

Varnish based on alkyd resins for the decoration and protection of exterior woodwork.

Solvent-based and colourless varnish which protects wood from water and UV damage.

Effectiveness

Xylazel Outdoor Varnish provides long term protection for exterior woodwork.

Xylazel Outdoor Varnish provides a clear rich finish which enhances the natural beauty of the wood.

Advantages

- High gloss finish.
- Thixotropic. Easy to apply.
- Excellent levelling properties.
- Touch drying: 3-6 hours.
- Excellent hardness and elasticity at the same time. It does not crack.

- It allows wood to breathe.
 - Resistant to most chemical agents, alcohol stains, greases.
- Washable.

- Low odour formula. Once dried, it does not smell.
- Excellent coverage: 12-15 m²/litre per coat.

Surfaces

Suitable for exterior wood, panelling, plywood, beams, pillars, doors, frames, windows, fences, furniture, handrails, wood panelling, skirting and any piece of wood.

Colours

Gloss finish: colourless.

Packaging: 375 ml, 750 ml, 4 L.

2. TECHNICAL DATA

Density at 20°C:

0,892-0,900 g/mL.

Viscosity Brookfield:

3,5 to 7 poises.

Inflammation point: >39°C.

Touch dry: 3-6 hours.

Second coat: 12 hours aprox.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

It is deemed necessary to apply one or two coats of Xylazel Wood Preserver to provide protection against decay, damp and insects.

Bare wood

Ensure the wood is clean and dry. Apply 2 coats. Lightly sand and clean dust between coats.

For previously varnished wood Remove any coating in a loose or poor condition.

Apply 1 or 2 coats of Xylazel Indoor Varnish. Lightly sand and clean dust between coats.

Coverage

67-83 mL/m² aprox. per coat under normal conditions.

Application

Xylazel Indoor Varnish is ready to use, you should not dilute it with solvent or any other product.

Stir the product thoroughly. Apply by brush, roller, airless or spray gun. Xylazel Indoor Varnish should be flowed on with the minimum of brushing and finished in the direction of the grain.

Recoat after 12 hours.

The can should be resealed after use and storage tightly closed to prevent evaporation of the product and entry of air.

Some local authorities have special facilities for disposing of waste coatings.

Treated wood

Once dry, Xylazel Outdoor Varnish does not increase the flammability of the wood.

Maintenance

For maintenance, sand wood to remove varnish coatings and apply Xylazel Outdoor Varnish.

Cleaning equipment

Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Apply in well ventilated areas until the treated timber is dry.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Store in a cool, dry, well ventilated place away from heat and sources of ignition.

Do not store when room temperature is over 30°C.

Do not empty into drains or watercourses.

5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



DIRECTION GENERALE
Jean-Pierre Escal MTR Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B.P. : 0526 Cotonou
contact@hpbenin.com
www.hpbenin.com

DIRECTION COMMERCIALE
HBP New City
Mouss Williams & Coeur de l'Inde
Tél.: (+229) 21 32 48 48
95 02 72 72 - 94 00 61 61

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com

