



# XYLAZEL AQUA WOODSTAIN

## Matt / Satin / Smooth

### 1. DESCRIPTION

#### Product Type

Alkyd/acrylic resins blend dispersed in water.

It is a quick drying woodstain which provides long term protection and decoration to exterior woodwork.

#### Advantages

- Xylazel Aqua Woodstain protects wood from the suns harmful UV rays, rain and humidity.
- It is highly water repellent.
- It does not crack, peel or flake.
- It penetrates deep into wood without building a barrier.
- It enhances natural wood grain.
- Easy maintain, there is no need to sand.
- Easy to apply by brush or spray gun.
- Quick drying.
- Fast drying formulation which allows rapid completion of any exterior project.
- Excellent adhesiveness.
- Low odour formula. Once dried, it does not smell.
- Mixable and transparent colours.

#### Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, furniture and any wood piece.

#### Colours

Matt and Satin: Colourless, Teak, Walnut, Mahogany, Oak, Pine, Wengue. Chestnut available only on satin finish.

Colorless finish should only be applied on sun exposure protected wood.

#### Packaging

750 ml and 5 litres

### 2. TECHNICAL DATA

#### XYLAZEL AQUA WOODSTAIN MATT

Density at 20°C:  
1.03±0.02g/mL.  
Touch dry: 30 min.  
Second coat: 2 hours.

#### XYLAZEL AQUA WOODSTAIN SATIN

Density at 20°C:  
1.01±1.04g/mL.  
Touch dry: 1 hour.  
Second coat: 2-3 hours.

#### XYLAZEL AQUA WOODSTAIN SMOOTH

Density at 20°C:  
1.04 ±0.02g/mL.  
Touch dry: 30 minutes.  
Second coat: 1 hour

### 3. USAGE GUIDE

#### Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

It is deemed necessary to apply Xylazel Wood Preserver to provide protection against decay and insects. In "oily" timbers such as teak and iroko, it is recommended to apply Xylazel Exotic Woods Primer.

#### Covering capacity

Matt: 150 to 200 mL/m<sup>2</sup>.  
Satin and Smooth: > 140 mL/m<sup>2</sup>.

#### Application

Stir the product thoroughly. Xylazel Aqua Woodstain is ready to use, you should not dilute it with solvent or any other product. For the possible finish use a good quality brush or a spray gun. Apply one or two coats. Lightly sand and clean dust between coats.

### Maintenance

Easy maintenance, there is no need to sand, simply apply more Xylazel Madex Woodstain when needed.

The period between maintenance application will vary and is dependent upon the degree of exposure, elevation, design of the component, quality of timber and original application.

The need for maintenance is indicated by lightening in colour and reduction in sheen as the coating erodes, and loss of water appearance.

Cleaning equipment  
Water.

### 4. OTHER INFORMATION

Apply in accordance with the coverage guidelines otherwise product performance will be reduced. Do not apply if the room temperature is below 5°C or over 30°C during application and drying or in conditions of high humidity.

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Do not empty into drains or water courses. Some local authorities have special facilities for disposing of waste coatings.

### 5. INFORMATION AND SERVICE

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assure responsibility for any work as the ultimate result depends on factors beyond our direct control.

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.



DIRECTION GÉNÉRALE  
Janquiss Face MTN Internet  
Tel.: (+229) 21 33 33 48  
95 96 00 08

04 BP - 0526, Cotonou  
contact@hpbenin.com  
www.hpbenin.com

DIRECTION COMMERCIALE  
HBP New City  
Mars Millaire, code de Postes  
Tel.: (+229) 21 32 48 48  
95 02 72 72 - 94 00 61 61

## xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n  
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

[www.xylazel.com](http://www.xylazel.com)

