

xylazel®

TOTAL IF-T Wood preservative

1. DESCRIPTION

Product Type

Xylazel Total IF-T is a clear protector of wood with organic solvents. It protects and cures against insects and xylophages fungi, includes termites.

Effectiveness

Xylazel Total IF-T effectively protects wood against rot fungi and xylophages insects (woodworm and termites). It acts as a curing protector for wood.

Advantages

- Xylazel Total gives wood an effective protection without changing its natural colour. This primer penetrates on wood guaranteeing its effectiveness.
- Easy to apply.
- It quickly penetrates into the wood.
- It improves adherence and length of finishes, protection the wood for a long time.

Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, garden furniture, wooden houses and any wood piece which humidity do not reach 20%.

Colour

Colourless.

Packaging

750 ml, 5 litres and 25 litres.

2. TECHNICAL DATA

Density at 20°C:

0,815-0,83 g/cm³ aprox.

Inflammation point: >55°C

Drying time: touch dry: 12 hours.

Recoatible: 24 hours aprox.

Drying times are dependent upon absorption of substrate and drying conditions.

Corrosion behaviour: It does not cause any rusting.

After drying, it can contact with plastics and bituminous substances.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed.

Xylazel Total is supplied ready to use. Do not thin. Apply the recommended dose in one or more coats until saturation is reached, with end grains this is best achieved by applying 'wet on wet' until the timber refuses to absorb any more. Once thoroughly dried Xylazel Total can be overcoated with woodstain varnish or paint.

Dose

140 mL/m²: Preventive efficacy against rot fungi.

300 mL/m²: eradicated efficacy against xylophages insects.

240 mL/m²: preventive efficacy against woodworm, bluestain fungi and termites.

Application

Apply by brush, dipping or immersion.

Bare wood

Ensure the wood is clean and dry. By brushing or dipping: apply before placing the wood in building site.

For previously varnished wood
Remove any coating in a loose or poor condition. Apply Xylazel Total until saturation is reached.

Finishing

Once dry, can be overcoated with most of decorative semi-transparent or opaque coating systems.

In case of doubt, try a test area first and allow to dry fully to ensure final appearance is acceptable.

The can should be resealed after use and storage tightly closed to prevent evaporation of the product and entry of air. Some local authorities have special facilities for disposing of waste coatings. Application by dipping: cover the container or bins. After applying remove the liquid and put it again into the original tin.

Use only steel or iron containers with a protective lacquer.

Once dry, Xylazel Total does not increase the flammability of the wood.

Now wood is protected against fungi, and woodworm.

CUSTOMER SERVICE



TEL.: +34 986 34 34 24
FAX: +34 986 34 64 24
avillar@xylazel.com
b.diaz@xylazel.com



DIRECTION GÉNÉRALE
Jonquet face MITN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B P : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Millaire à côté de Toi Lobo
Tél.: (+229) 21 32 43 48
95 02 72 72 - 94 00 61 61

xylazel
xylazel.com



Gándaras de Prado - Budiño s/n
Apartado 91. 36400 Porriño (Pontevedra)
Telf.: 986 343 424. Fax: 986 346 240



Cleaning equipment
Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Xylazel Total contains biocides to protect wood against xylophagous insects (woodworm).

Use biocides safely. Always read the label and product information before use.

Apply in well ventilated areas until the treated timber is dry.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Material Safety Data Sheet covering every Xylazel products are supplied to our customers and are freely available to users on request.

Storage and manipulation
Do not store when room temperature is below 5°C or over 30°C.

Do not empty into drains or watercourses.

Do not use on beehives, bee keeping equipment or saunas.

5. INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

CUSTOMER SERVICE



TEL.: +34 986 34 34 24
FAX: +34 986 34 64 24
a.villar@xylazel.com
p.diaz@xylazel.com

xylazel
xylazel.com

Gándaras de Prado - Budiño s/n
Apartado 91. 36400 Porriño (Pontevedra)
Telf.: 986 343 424. Fax: 986 346 240

