



WATER BASED WOOD PRESERVER

1. DESCRIPTION

Product Type

Water based timber preservative for providing protection against wood-destroying fungi, blue stain, insects and humidity. Water repellent.

It penetrates deep into wood without building a barrier. Use as a basecoat before painting staining or varnishing.

Advantages

· Xylazel Water-based Wood Preserver is a colourless general-purpose preserver for the combined eradication of the two main enemies of timber – rot and insect attack.

- Quick drying Wood Preserver. It allows finish jobs the same day.
· It gives deep penetrating protection to sound wood.

- It quickly penetrates into the wood. Easy to apply.

· It provides a colourless treatment that can be overcoated with Xylazel woodstains, paints and varnishes.

- Low odour formula. Once dried, it does not smell.

- It does not crack, peel or flake.

Efficacy

- Use classes 1, 2 & 3 of EN 335.

- UNE-EN46: Stipulation of effective prevention against new born *Hylotrupes bajulus* (Linnaeus) larvae.

EN73 Accelerated ageing tests of treated woods before biological testing. Evaporation experiment. EN84 Accelerated ageing tests of treated woods before biological testing.

Fading experiment.
- UNE-EN 113: Stipulation of efficiency threshold against *Xilofages* Basidiomycete fungus cultivated in dry conditions.

- UNE-EN 152-1: Wood preservatives - Determination of the protective effectiveness of a preservative treatment against blue stain in wood in service - Laboratory method

Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, furniture and any wood piece.

It is suitable for exterior woodwork, providing a preservative treatment against woodworm and fungi.

Colour

Colourless only.

Packaging

25, 120 and 1000 litres.

2. TECHNICAL DATA

Density at 20°C:

1,00 g/cm³ ± 0.02.

Viscosity: very fluid.

Drying time: touch dry: 1 h. aprox.

Recoatable: 3 hours aprox.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed. Lightly sand to remove any loose wood fibres, paints or varnishes.

Xylazel Water Based Wood Preserver is supplied ready to use. Do not thin. Apply the recommended dose in one or more coats until saturation is reached, with end grains this is best achieved by applying 'wet on wet' until the timber refuses to absorb any more.

Dose

200 mL/m² one or more coats.

Application

Apply by brush, spray gun or short-time immersion (dipping).

Cleaning equipment

Water and soap.

4. OTHER INFORMATION

Storage and manipulation

Do not store when room temperature is below 5°C or over 30°C.

Do not empty into drains or watercourses.

5. INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Material Safety Data Sheet covering every Xylazel products are supplied to our customers and are freely available to users on request.



DIRECTION GÉNÉRALE
Jouquet Face MTN Internet
Tel.: (+229) 21 33 33 48
99 96 00 08

04 B P - 0526 Cotonou
contact@hpbenin.com
www.hpbenin.com

DIRECTION COMMERCIALE
HBP New City
Mimo Millier & Co. de SaoLobo
Tel.: (+229) 21 32 48 48
99 02 7272 - 94 00 61 61

xylazel, s.a.

APARTADO 91 - GANDARAS DE PRADO, s/n
36400 PORRIÑO (PONTEVEDRA)

TEL.: +34 986 34 34 24

FAX: +34 986 34 64 17

www.xylazel.com

