



WOODWORM KILLER

1. DESCRIPTION

Product Type

Xylazel Woodworm killer is specially formulated to eradicate and prevent woodworm attack.

Composition

Permethrin 0,22%
Solvent csp 100%

Effectiveness

Xylazel Wood Preserver is effective on timber prevention and eradication of woodworm.

Advantages

- Clear solvent based formula. It penetrates deep into wood providing long term protection.
- Easy to apply.
- It quickly penetrates into the wood without building a barrier.
- Low odour formula. Once dried, it does not smell.

Surfaces

Suitable for interior and exterior joinery, hardwoods, softwoods, cladding, beams, pillars, doors, frames, windows, fences, garden furniture, wooden houses and any wood piece.

Colour

Colourless only.

Packaging

750 ml, 5 litres and 25 litres.
200 ml and 400 ml aerosol.

2. TECHNICAL DATA

Density at 20°C:

0,794 g/cm³ aprox.

Viscosity: very fluid.

Drying time: touch dry: 12 hours.

Recoatible: 24 hours aprox.

Drying times are dependent upon absorption of substrate and drying conditions.

Corrosion behaviour: It does not cause any rusting.

After drying, it can contact with plastics and bituminous substances.

3. USAGE GUIDE

Preparation

Surface must be suitably prepared, clean and dry, with dust, dirt, wax and grease removed.

Xylazel Woodworm Killer is supplied ready to use. Do not thin. Apply the recommended dose in one or more coats until saturation is reached, with end grains this is best achieved by applying 'wet on wet' until the timber refuses to absorb any more.

In severe cases, also inject into flight holes by injection.

In varnished surfaces do not apply by brush.

Once thoroughly dried Xylazel Woodworm Killer can be overcoated with woodstain varnish or paint.

Dose

200 mL/m²: Preventive efficacy against woodworm, 2 or more coats.

300 mL/m²: eradicated efficacy against woodworm, 2 or more coats.

Application by injection, press the valve several times until fill the holes and clean excess product.

Application

Apply by brush, dipping or immersion.

Aerosol: by spray or injection.

Bare wood

Ensure the wood is clean and dry.

By brushing or dipping: apply before placing the wood in building site.

For previously varnished wood

Remove any coating in a loose or poor condition. Apply Xylazel Woodworm Killer until saturation is reached.

Finishing

Once dry, can be overcoated with most of decorative semi-transparent or opaque coating systems.

In case of doubt, try a test area first and allow to dry fully to ensure final appearance is acceptable.

The can should be resealed after use and storage tightly closed to prevent evaporation of the product and entry of air. Some local authorities have special facilities for disposing of waste coatings.

Application by dipping: cover the container or bins. After applying remove the liquid and put it again into the original tin.

Use only steel or iron containers with a protective lacquer.

Treated wood

Once dry, Xylazel Wood Preserver does not increase the flammability of the wood.

Now wood is protected against fungi, and woodworm.

Cleaning equipment

Xylazel Thinner or White Spirit.

4. OTHER INFORMATION

Xylazel Woodworm Killer contains biocides to protect wood against xylophagous insects (woodworm).

Apply in well ventilated areas until the treated timber is dry.

Apply in accordance with the coverage guidelines otherwise product performance will be reduced.

Material Safety Data Sheet covering every Xylazel products are supplied to our customers and are freely available to users on request

CUSTOMER SERVICE



TEL.: +34 986 34 34 24
FAX: +34 986 34 64 24
a.villar@xylazel.com
b.diaz@xylazel.com



DIRECTION GÉNÉRALE
Jonquet Face MTN Internet
Tél.: (+229) 21 33 33 48
95 96 00 08

04 B.P. : 0526 Cotonou
contact@hbpbenin.com
www.hbpbenin.com

DIRECTION COMMERCIALE
HBP New City
Maro Militaire à côté de Toki Lobo
Tél.: (+229) 21 32 43 48
95 02 72 72 - 94 00 61 61

xylazel
xylazel.com



Gándaras de Prado - Budiño s/n
Apartado 91. 36400 Porriño (Pontevedra)
Telf.: 986 343 424. Fax: 986 346 240



Use biocides safely. Always read the label and product information before use.

Storage and manipulation

Do not store when room temperature is below 5°C or over 30°C.

Do not empty into drains or watercourses.

Do not use on beehives, bee keeping equipment or saunas.

5. INFORMATION AND SERVICE

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

CUSTOMER SERVICE



TEL.: +34 986 34 34 24
FAX: +34 986 34 64 24
a.villar@xylazel.com
p.diaz@xylazel.com

xylazel
xylazel.com

Gándaras de Prado - Budiño s/n
Apartado 91.36400 Porriño (Pontevedra)
Telf.: 986 343 424. Fax: 986 346 240

